

DATA SHEET

Dispensing Accessories

Features

- Color coded for easy identification
- Durable materials
- Fits any standard syringe
- Competitive Prices

Benefits

- Compatible with all Nordson EFD & Fishman systems
- Premier line of tips are burr-free for consistent flow
- Ensure Accuracy, Repeatability & Productivity

Applications

- Automated Dispensing
- Manual Syringes
- Telecommunications, Military Medical or Broadcast connectors

Connected Fibers offers a large variety of dispensing accessories for your manual and automated dispensing needs. Our components are silicone and chloride free and work with industry standard equipment. Maximum operating pressure is 100psi (6.9bar). This premier line of dispensing tips is burr-free, and has an electro-polished cannula for unobstructed and consistent material flow. Pistons ensure pressure is evenly spread across the fluid surface to provide consistent dispensing. The pistons provide a complete seal for low viscosity fluid. Tip caps seal syringe barrel tip during storage, or while using in centrifuge.



Color	Gauge
Olive	14
Amber	15
Green	18
Pink	20
Purple	21
Blue	22
Orange	23
Red	25
Clear	27
Lavender	30
Yellow	32

Standard Dispensing Tips			
Gauge	Length 0.5"	Length 1"	Length 1.5"
14	SDT14050	SDT14100	SDT14150
15	SDT15050	SDT15100	SDT15150
18	SDT18050	SDT18100	SDT18150
20	SDT20050	SDT20100	SDT20150
21	SDT21050	SDT21100	SDT21150
22	SDT22050	SDT22100	SDT22150



Syringe Barrel, Piston, Tip Cap				
Vol.	Clear Syringe	White Piston	White Tip Cap	Kit
3cc	SB03C	SP03W	STC00W	SBCPWTC03-KIT
5cc	SB05C	SP05W		SBCPWTC05-KIT
10cc	SB10C	SP10W		SBCPWTC10-KIT

*Sold in
Packs
of 100pcs*

Also available:



**Piranha EPO-TEK
353ND Epoxy**



Call now to place
your order:
1-866-899-7953



Syringe Barrel Adapter Assembly	
Vol.	Yellow
3cc	SBA03Y
5cc	SBA05Y
10cc	SBA10Y

Tel: 1-866-899-7953 • Fax: 678-623-0652 • Sales@ConnectedFibers.com • www.ConnectedFibers.com

Connected Fibers, LLC MAKES NO EXPRESS OR IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS OR OTHERWISE, with respect to its products. In addition, while the information herein is believed to be reliable, no warranty is expressed or implied regarding the accuracy of the data or the results to be obtained from the use thereof. All recommendations or suggestion for use are made without guarantee - inasmuch as conditions of use are beyond our control. The properties given are typical values, and are not intended for use in preparing specifications. Users should make their own test to determine the suitability of this product for their own purposes. Prices subject to change without notice. All statements, technical information related to the Seller's products are based on the information believed to be reliable, but the accuracy or completeness thereof is not guaranteed.